

FIBERLAUNCH™

flexible - automatic - fiber optic launch cable



PH PALDEN GmbH Deutschland
Geschäftsführer: Thomas Resovsky
T: +49 (0) 89 45835-400
F: +49 (0) 89 45835-401
office@phpalden.de
www.phpalden.de



FIBERLAUNCH™



FIBERLAUNCH™

flexible - automatic - fiber optic launch cable

From now on connecting the launch cable from OTDR measurement to installed fibres will be more efficient, secure and above all extremely fast and easy

Especially for FTTH installations an increasing amount of connectors have to be measured on very different spots and locations

Therefore it is becoming more and more important to use a robust, handy and easy-to-use launch fibre

With the patented Flexi System and automatic stop the duration of every single measurement will be reduced up to 3 minutes each



www.fiberlaunch.com

PH PALDEN GmbH Deutschland
Geschäftsführer: Thomas Resovsky
T: +49 (0) 89 45835-400
F: +49 (0) 89 45835-401
office@phpalden.de
www.phpalden.de



FIBERLAUNCH™



products

FIBERLAUNCH™

CC2 small

The FIBERLAUNCH CC2 is small, cost effective and with its non armoured launch cables ready for reassemble the connectors after damage or losing loss quality

Length: 50m-300m, 150m Standard



Standard

The FIBERLAUNCH STANDARD is robust, cost effective and has protected connectors.

With its non armoured launch cables it is ready for reassemble the connectors after damage or losing loss quality

Length: 50m-1000m, 500, 1000m Standard



High Quality

Our FIBERLAUNCH HQ is a high-end product with steel armoured launch cables, Corning fibres and certified 0,1dB HQ Connectors for high-level proficiency.

To each assembled connector we provide a detailed measurement protocol (IL,RL)

Length: 50m-1000m, 500, 1000m Standard



All FIBERLAUNCH are available with all different fibres
OM1, OM2, OM3, OM4, G652.D, G.657, LEAF...



technical data

FIBERLAUNCH	CC2	STANDARD	HIGH QUALITY
length	Standard 150m Option: 50m-300m	Standard 500m, 1000m Option: 50-1000m	Standard 500m, 1000m Option: 50-1000m
fiber	Corning, all fibres	Corning, all fibres	Corning, all fibres
wavelength	MM: 850nm, 1300nm SM: 1310nm, 1550nm	MM: 850nm, 1300nm SM: 1310nm, 1550nm	MM: 850nm, 1300nm SM: 1310nm, 1550nm
connectors	all standard connectors	all standard connectors	all standard connectors
attenuation/connector	IL: max. -0,20 dB RL: UPC >50dB, APC >65dB	IL: max. -0,20 dB RL: UPC >50dB, APC >65dB	IL: max. -0,10 dB RL: UPC >50dB, APC >65dB
mating cycles	min. 1000 cycles	min. 1000 cycles	min. 1000 cycles

FL-XX-XX-XX/X-XX/X-XXX

purchase information

type

CC2 = small
STD = Standard
HQ = High Quality

polish

A = APC

polish

A = APC

length

150 = 150m
500 = 500m
1000 = 1000m

connector A connector B

FC	FC
SC	SC
LC	LC
ST	ST
E2 (E2000)	E2 (E2000)
F3 (F3000)	F3 (F3000)
LX (LX.5)	LX (LX.5)

fibre

9 = SM G652.D
50 = 50/125 OM3
62 = 62,5/125
97 = SM G657
9L = LEAF
54 = OM4

FIBERLAUNCH distributor for your country:

www.fiberlaunch.com